

MANU'

WATER BASED WAX

DESCRIPTION:

MANU' is a water based wax for the finishing and maintenance of surfaces. This wax performs good stain-proof features and also protects the treated surface from dirt and from foot traffic, enhancing the brightness of the treated material. It is vapor permeable and resistant to UV rays, therefore it is not yellowing if exposed to direct sunbeams. The product forms neither accumulations nor requires a periodic stripping.

MANU' is especially recommended to make an extra-ordinary maintenance of any type of waxed floor, diluted into the cleaning solution.

ADVANTAGES:

- High resistance to foot traffic
- Transpiring
- Makes maintenance simple
- Enhances brightness
- Protects the surface from several stains


WHERE TO APPLY:

Only for interior surfaces. Terracotta tiles, rough marbles and granites, structured ceramic and materials that are porous enough to allow a good adhesion. For much absorbing materials, such as hand made cotto and terracotta tiles, it is necessary to apply the product only after treating the material with an undercoat impregnator such as AC 300, DREP or HIDRO 150.

COVERAGE:

15-20 sq m/l (referring to the type of material)

CAN BE APPLIED WITH:



USE:

The product can be diluted only in case of treatment of porcelain stoneware or in case of periodic maintenance of a treated surface.

FIRST APPLICATION:

Apply a thin even coat of product to a dry and clean surface with a soft cloth, a mop or a lambs wool, avoiding any excess and caring for an even distribution.

After applying the product, allow the floor to dry 4 hours at least before restoring the foot traffic. Should one only coat of product prove not to be enough, it will be possible to apply a further coat, repeating the operation after 4 hours.

MAINTENANCE

This polymer needs a periodic maintenance, that will be as frequent as much intense the foot traffic or stress on the floor is.

It will only be needed to wash the floor when required (when a deterioration can be remarked), with a solution of MANU' diluted in water at 15% to 20%, with a mop, a rug or a lambs wool, leaving on the surface a thin even veil of product. Repeat the application any time it is necessary.

WWW.FABERCHIMICA.COM

Faber Chimica s.r.l. – Loc. Campo d'Olmo Via G. Ceresani, 10 60044 Fabriano (AN) – ITALY
Tel. +390732-627178 Fax +390732-22935 E-mail: info@faberchimica.com
www.faberchimica.co

TECHNICAL DATA:

Aspect	: Liquid
Color	: White
Odor	: Typical
pH (5% solution)	: 8.0 ± 0.5
Specific gravity (20 °C)	: 1000 ± 10 g/l
Flash point (ASTM D 56)	: not flammable

STORAGE:	Keep the container closed and in a cool place .
SHELF LIFE:	24 months in the original sealed packing and kept in a cool and dry place.
PACKAGING:	1 lt. bottles (12 per carton) - 5 lt. containers (4 per carton)

THINGS TO AVOID: **DO NOT APPLY ON ACIDIFIED SURFACES.**

SAFETY:

- S2 : Keep out of the reach of children
- S24 : Avoid contact with skin
- S25 : Avoid contact with eyes

THOUGH THE INFORMATION ON THIS SHEET ARE THE RESULTS BOTH OF OUR RESEARCH AND OPERATIONAL TECHNICAL EXPERIENCE, THEY CANNOT BE CONSIDERED UNDERTAKING OR INVOLVE OUR RESPONSIBILITY AS THE CONDITIONS REQUIRED FOR THE APPLICATION CANNOT BE SUPERVISED BY US. FABER CHIMICA S.R.L. DOES NOT PROVIDE ANY WARRANTY, EITHER EXPRESS OR IMPLIED AND DOES NOT ASSUME ANY RESPONSIBILITY CONCERNING THE USE OF THESE DATA AND SUGGESTIONS.

Rev. Nr. 0.1

Date: 04/02/2012

WWW.FABERCHIMICA.COM

Faber Chimica s.r.l. – Loc. Campo d'Olmo Via G. Ceresani, 10 60044 Fabriano (AN) – ITALY
Tel. +390732-627178 Fax +390732-22935 E-mail: info@faberchimica.com
www.faberchimica.com